

JEDYNKA® FASADOWABIAŁA WITH POSSIBILITY TO TINTING ACRYLIC PAINT FOR FACADES AND INTERIORS



- ✓ Durable colours
- ✓ resistant to atmospheric conditions
- ✓ easy application
- ✓ Effect of unified surface, no brush smudges
- ✓ Ecological recipe
- ✓ great coverage: approx.: 8 m²/l per one coat

PRODUCT DESCRIPTION

Ecological dispersion, acrylic paint for exterior and interior application. It creates matt surfaces resistant to atmospheric conditions, gives long lasting decorative effect. Product has very good adhesion to the surface. Micro-porous coat of paint ensure micro ventilation of painted surface.

EXAMPLES OF USE

Product is used for decorative and protective application on exterior cement and cement-lime plasters, as well as walls and ceilings in living quarters, office spaces and public buildings and for decorative painting of concrete surfaces.

APPLICATION

1) PREPARATION OF THE SURFACE

New, unpainted surfaces must be dry and thoroughly cleaned of any flaking paint, dust, grease and other dirt, which can impair adhesive power of paint. New plaster and concrete substrates can be painted after 4 weeks of seasoning (we recommend to wait with painting of new buildings after the first heating season, during this time the construction humidity will evaporate), after priming with JEDYNKA® FASADOWA thinned with water up to 30%. In case of renovation remove any flaking old paint, work chalked substrates through sandblasting and glossy surfaces matt down with sanding, then surfaces should be dusted and washed with water prior to painting. Layers of lime and glue paint have to be removed completely to uncover plaster. Uneven surfaces, cracks should be even with cement-lime filler and after that primed with thinned paint.

2) PAINTING

Paint can be applied with brush, roller or airless spray.

Before application paint should be well stir. Product does not require thinning. It is recommended to apply 2-3 coats. It's not allowed to add to the product lime or chalk. The paint is dry after approx. 2 hours. Consecutive coats can be applied not earlier than after 4 hours. Painting should be performed at the temperature from +5°C to +25°C.

Notice! To avoid differences with shades please use paint from one production batch.

THINNER/TOOLS CLEANING

Wipe away excessive paint from the tools before cleaning. Thinner/ tools cleaning: water.

COLOURS

White as a base tintible to 237 shades.

GLOSS GRADE

Matt

COVERAGE

Up to 8 m²/l per coat. Actual spreading rates will depend upon absorbing capacity of the substrate and application method.

SHELF LIFE

36 months from production date, stored in originally closed container.

PACKAGING

White/base – 0,9l; 2,7l; 9l

ENVIRONMENTAL

Keep out of the reach of children. During application wear suitable working clothes and protective gloves. Closed areas should be well aired after application until the odour is gone, then they can be used. Wipe away excessive paint from the tools before cleaning. Empty cans as well as cans with remains of paint should be given to special point where such waste are collected. Precise information about waste disposal can be found in local municipality office. Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 1,2-benzisothiazol-3(2H)-one (BIT) and 2-methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains 2-methyl-2H-isothiazol-3-one (MIT), 1, 2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). Safety Data Sheet available at Client request.

TRANSPORT AND STORAGE

Transport and storage in tightly closed containers in temperatures from +5°C to +25°C. Storage in dry and airy rooms. Notice! Protect from frost and direct sunlight.

TECHNICAL PARAMETERS

Viscosity (+23°C) KU	100-110
Density	approx. 1,5 g/cm ³
Drying time at temp. +23°C	2 – 3 hrs.

ADDITIONAL INFORMATION

Cat. A/c. Acceptable VOC content since 2010. - 40 g/l.

Cat. A/a. Acceptable VOC content since 2010. - 30 g/l. Product contain below: 30 g/l VOC.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.